

# InfiniSolar WP 3ph 10KW-15KW



- IP65 waterproof and dustproof makes the inverter available for various working conditions.
- Built-in WiFi for mobile monitoring (App is available)
- 150% unbalanced load support
- Optional dual outputs for smart load management (check sales)
- Built-in AC coupled function
- User-adjustable charging current and voltage
- Reserved communication port for BMS (RS485)
- Parallel operation up to 6 units

## InfiniSolar WP Three Phase On-Grid Inverter with Energy Storage Selection Guide

MODEL	InfiniSolar WP 10KW	InfiniSolar WP 12KW	InfiniSolar WP 15KW
<b>MAXIMUM PV INPUT POWER</b>	14500 W	16000 W	22500 W
<b>RATED OUTPUT POWER</b>	10000 W	12000 W	15000 W
<b>MAXIMUM CHARGING POWER</b>	10000 W	12000 W	15000 W
<b>GRID-TIE OPERATION</b>			
<b>PV INPUT (DC)</b>			
Nominal DC Voltage / Maximum DC Voltage	720 VDC / 1000 VDC	720 VDC / 1000 VDC	720 VDC / 1000 VDC
Start-up Voltage / Initial Feeding Voltage		320 VDC / 350 VDC	
MPP Voltage Range	350 ~ 950 VDC	350 ~ 950 VDC	350 ~ 950 VDC
Number of MPP Trackers / Maximum Input Current	2 / A: 27A, B: 27A	2 / A: 27A, B: 27A	2 / A: 27A, B: 27A
Number of Strings Per MPP Tracker	A: 2, B: 2	A: 2, B: 2	A: 2, B: 2
<b>GRID OUTPUT (AC)</b>			
Nominal Output Voltage		230 VAC (P-N) / 400 VAC (P-P)	
Output Voltage Range		184 - 265 VAC per phase	
Nominal Output Current	14.5 A per phase	17.4 A per phase	21.7 A per phase
Power Factor range		0.9 lag ~ 0.9 lead	
<b>EFFICIENCY</b>			
Maximum Conversion Efficiency (DC/AC)		>96%	
European Efficiency@ Vnominal		>95%	
<b>OFF-GRID OPERATION</b>			
<b>AC INPUT</b>			
AC Start-up Voltage / Auto Restart Voltage		120 - 140 VAC / 180 VAC	
Acceptable Input Voltage Range		170 - 290 VAC per phase	
Maximum AC Input Current	40 A	40 A	40 A
<b>PV INPUT (DC)</b>			
Maximum DC Power	14500 W	16000 W	22500 W
Maximum DC Voltage	1000 VDC	1000 VDC	1000 VDC
MPP Voltage Range	350 ~ 950 VDC	350 ~ 950 VDC	350 ~ 950 VDC
Number of MPP Trackers / Maximum Input Current	2 / A: 27A, B: 27A	2 / A: 27A, B: 27A	2 / A: 27A, B: 27A
Number of Strings Per MPP Tracker	A: 2, B: 2	A: 2, B: 2	A: 2, B: 2
<b>BATTERY MODE OUTPUT (AC)</b>			
Nominal Output Voltage		230 VAC (P-N) / 400 VAC (P-P)	
Output Waveform		Pure sine wave	
Efficiency (DC to AC)	91%	91%	91%
<b>HYBRID OPERATION</b>			
<b>PV INPUT (DC)</b>			
Maximum DC Voltage	14500 W	16000 W	22500 W
Start-up Voltage / Initial Feeding Voltage		320 VDC / 350 VDC	
MPP Voltage Range	350 ~ 950 VDC	350 ~ 950 VDC	350 ~ 950 VDC
Number of MPP Trackers / Maximum Input Current	2 / A: 27A, B: 27A	2 / A: 27A, B: 27A	2 / A: 27A, B: 27A
Number of Strings Per MPP Tracker	A: 2, B: 2	A: 2, B: 2	A: 2, B: 2
<b>GRID OUTPUT (AC)</b>			
Nominal Output Voltage		230 VAC (P-N) / 400 VAC (P-P)	
Output Voltage Range		184 - 265 VAC per phase	
Nominal Output Current	14.5 A per phase	17.4 A per phase	21.7 A per phase
<b>AC INPUT</b>			
AC Start-up Voltage / Auto Restart Voltage		120 - 140 VAC / 180 VAC	
Acceptable Input Voltage Range		170 - 290 VAC per phase	
Maximum AC Input Current	40 A	40 A	40 A
<b>BATTERY MODE OUTPUT (AC)</b>			
Nominal Output Voltage		230 VAC (P-N) / 400 VAC (P-P)	
Efficiency (DC to AC)	91%	91%	91%
<b>BATTERY &amp; CHARGER</b>			
Battery Voltage Range	40 ~ 62 VDC	40 ~ 62 VDC	40 ~ 62 VDC
Maximum Charging Current	200 A	250 A	300 A
<b>GENERAL</b>			
<b>PHYSICAL</b>			
Dimension, D x W x H (mm)		255 x 660 x 750	
Net Weight (kgs)	70	70	73
<b>INTERFACE</b>			
Communication Port		RS-232, RS-485, USB, CAN and Wi-Fi	
Intelligent Slot		Optional for SNMP and Modbus cards	
<b>ENVIRONMENT</b>			
Humidity		0 ~ 100% RH (Non-condensing)	
Operating Temperature		-25 to 60°C, > 45°C power derating	
Altitude		0 ~ 1000 m**	

\*These figures are based on VDE-4105 standard. All figures may vary depending on different AC voltage and country requirements.

\*\* Power derating 1% every 100 m when altitude is over 1000m.  
Product specifications are subject to change without further notice.