

SOLERON

120/160/210/240M



SOLERON Solar Modules

Features



Guaranteed 0- +5W positive power output tolerance ensures high reliability



Anti-reflective, hydrophobic coating improves light absorption and reduces surface dust



Excellent performance under low light environments (mornings, evenings and cloudy days)



Entire module certified to withstand high wind loads (2400 Pascal) and snow loads (5400 Pascal)*



POWER (Pmax)	OPEN CIRCUIT VOLTAGE Voc(V)	SHORT CIRCUIT CURRENT Isc(A)	PEAK VOLTAGE Vmp(V)	PEAK CURRENT IMP (A)	SIZE (mm)	CELL Quantity	NET WEIGHT (kg)
120W	29,10	5,87	21,62	5,55	825*705*30		
160W	31,38	5,87	28,87	5,55	1065*705*30		
210W	22,56	11,87	18,87	11,12	1405*705*30		
240W	25,38	11,87	21,58	11,12	1575*705*30		

Industry-leading warranty

- 25 year transferable power output warranty: 10year/90%; 25year/80%.
- Based on nominal power.
- 10 year material and workmanship warranty.

ELİZLER ENERJİ VE TEKNOLOJİ SANAYİ VE TİCARET ANONİM ŞİRKETİ

Add : Kemalpasa OSB Mah. 625 Sk. No:6 Kemalpasa/İzmir ,Turkey

E-mail: info@elizler.com
www.elizler.com