



Flexible installation, saving time and effort



1C/1C continuous charge and discharge



5 years standard warranty



Superior LiFePO4 safety performance



Low voltage safety connection



Max. 16 modules parallel

Compatible With Inverter Brands

GenixGreen's battery BMS supports simultaneous communication and compatible with multiple inverter brands
























Parameters

Product Model	ES-BOX12S
Nominal Energy	5.12kWh
Nominal Voltage	25.6V
Nominal Capacity	200Ah
Cell Type	LFP
Standard Charge Voltage	28.4V
Max. Discharge Current	100A
Discharge Cut-Off Voltage	22.4V
Parallel Function	RS485
Communication Interface	RS485、USB、CAN
Cycle Life *	≥6000 Cycles (25°C±2°C, 0.5C, 80%DOD@65%EOL)
Charge Temperature Range	0~55°C
Discharge Temperature Range	-20~55°C
Certification	Pack: CE/MSDS/UN38.3 Cell: CE/IEC 62619 by TUV/UL1973 by Intertek/ROHS
Dimension	480*600*150mm
Net Weight	45Kg
Installation Method	Wall Mounted/Floor Standing
Warranty	5 Years(Under Warranty Terms)
Energy Throughput ⁽¹⁾	11MWh
Optional	WiFi Remote Monitoring

[1] Conditions apply, refer to our company warranty letter.

www.ventaenerji.com © Hegel