

2-WAY SPEAKER

MAC 15

15" 2-WAY PASSIVE SPEAKER

DESCRIPTION

MAC 15 is a multipurpose two-way full-range professional speaker system, suitable for a wide range of applications, such as live sound reinforcement and stage monitoring as well as distributed sound systems for clubs or music venues.



WOOFER



Max SPL



TWEETER



Max POWER



FEATURES

- Power-1000W Max.
- 99dB max SPL
- 70Hz-16kHz Frequency Response
- 15" Woofers, 2.5" VC
- 1" Tweeter, 1.75" VC

Klangmeister



MAC 15

DATASHEET

Technical Specifications

Electronic specifications	Frequency Response (-10dB):	70 Hz ÷ 16 kHz
	Max SPL@1m:	130dB
	Horizontal Coverage Angle:	90°
	Vertical Coverage Angle:	60°
	System Sensivity:	99dB
Audio Power	Amplification:	Full Range
	AES:	500W
	Program:	1000W
	Nominal Impedance:	8Ω
	Crossover Frequency:	1900Hz
	Recommended Amplifier:	KX4000, KXT5000
Transducers	Woofers:	15", 2.5" Voice Coil
	Tweeter:	1", 1.75" Voice Coil
Input/Output Section	Input Connector:	Speakon-NL4
	Output Connection:	Speakon-NL4
Standard compliance	Safety agency:	CE compliant
Physical Specifications	Cabinet/Case Material:	PP
	Handles:	2 side
	Grill:	Metal
	Color:	Black
Dimensions	Height:	75cm
	Width:	48.2cm
	Depth:	39.5cm