COLUMN SPEAKER



DESCRIPTION

CX-83A is a compact and elegant fullange column speaker providing highly intelligible voice reproduction, and suitable for installation into places of worship, stations, subways and many other environments.



109 dB Max SPL







FEATURES

- Power-320W Max.
- 109dB max SPL
- 140Hz-16kHz Frequency Response
- 3" Full range Woofers, 0.75" VC
- Full Aluminium Body









Electronic specifications	5 Frequency Response (-10dB):	140 Hz ÷ 16 kHz
	Max SPL@1m:	109dB
	Horizontal Coverage Angle:	150°
	Vertical Coverage Angle:	30°
	System Sensivity:	92dB
Audio Power	Amplification:	Class D
	AES:	160W
	Program:	320W
	Nominal Impedance:	13.7Ω
Transducers	Full Range:	3", 0.75" Voice Coil
Input/Output Section	Input Connector:	1 pcs XLR Con.
	Output Connector:	1 pcs XLR Con.
	Power Connector:	1 pcs Powercon
Standard compliance	Safety agency:	CE compliant
Physical Specifications	Cabinet/Case Material:	Full Aluminium
	Handles:	-
	Grill:	Metal
	Color:	Black and White
Package Dimensions	Height:	80.6cm
	Width:	11.0cm
	Depth:	13.5cm