



LINEAR MODULE

LM-F005-LNR

PRODUCT DESCRIPTION

Constant Current Led Board
Current Range = 200 mA - 350 mA
Power Range = 20 - 36 watt
Lumen = 2800 - 5400lm
Holes for screw fixing and or / biadhasive thermal pad optional
Led Chip : On customer demand, Lumileds, Samsung, Cree, Seoul, Nichia etc
solid conductor for input voltage
Optional Accessories : lens, Drivers, Housing

Dimension 16 X 1188 mm as shown
Led Case 2835
PCB 1mm FR4 35um
LED QTY 108
Operating Temp: -40 °C 105 °C
Origin Turkey
Warranty 2 years

PRODUCT CODE	OPERATING MODE	COLOUR TEMP	LEDS	SERIAL	PARALEL	LUMIOUS FLUX	MIN FORWARD VOLTAGE	MAX VOLTAGE	MAX POWER CONSUMPTION	COLOUR RENDERING INDEX
LM-F005-LNR	200 mA	3000K	108	36	3	2800	102 V	115 V	20W	>70
		4000K				2900	102 V	115 V	20W	>70
		6500K				3000	102 V	115 V	20W	>70
LM-F005-LNR	350 mA	3000K	108	36	3	4800	102 V	115 V	36W	>70
		4000K				5100	102 V	115 V	36W	>70
		6500K				5400	102 V	115 V	36W	>70

