



- ❖ Enec Driver ,Flicker Free
- ❖ PC Extrusion Body
- ❖ 5 years warranty
- ❖ Suitable for harsh environmental conditions




Mechanical Spesifications						Optical Specifications				
Body	PC					Light Source	MidPower Led			
Ip Raiting	IP65					Reflector	-			
IK Rating Body	IK 06					Lens	-			
Ral Code	RAL 7040					Diffuser	PC Opal			
Cable Gland	PG7					CRI	>80			
Cable	3x0,75 mm2					Colour Temperature	3000K / 4000K / 6500K			
Fire Protection	650°C					Photobiological Risk Group	RG1			
Mounting Type	Cable Tray/Surface Mounted					Beam angle	120°			
Electrical Specifications						Options				
Input Voltage	220-240 VAC					DALI	✓			
Power Factor	>0.95					1-10 V	✓			
System Lifetime	50000h					1 Hour Emergency Kit	✓			
Class	II					3 Hour Emergency Kit	✓			
Operating Temperature	-20°C / +45°C					Microvave Sensor				
Standards	LM79/LM80				Another Mounting Type					
ERP Code	Ceiling Type	Power(W)	Efficiency(lm/W)	Luminous Flux(lm)	Colour Temp.	Dimensions (mm)	Cut Size	Pcs/Pack	Pack Weight(kg)	Accessory
1910100	Surface	18W	110	1980	3000K / 4000K / 6500K	50x56x600		12	6,5	Mounting Spring
1910101	Surface	36W	110	3960	3000K / 4000K / 6500K	50x56x1200		12	11	Mounting Spring
1910102	Surface	50W	110	5500	3000K / 4000K / 6500K	50x56x1480		12	13,5	Mounting Spring





Technical Drawing Teknik Çizim



Light Distribution Curve Işık Şiddeti Dağılım Eğrisi

